

3M Fire Protection Products
3M™ Fire Barrier Putty Sleeve Kits



Versatile, Dual Protection One Complete Kit



Whether used in new construction or renovation projects, everything you need is in one complete kit.

The 3M™ Fire Barrier Putty Sleeve Kit contains all the components required to meet firestop code for installation of cable and blank applications. Innovative sleeve design delivers both fire and cable protection and helps ensure smooth cable entry and no-slip installations. Easy-slit label on sleeve allows quick splitting for retrofitting around existing cables. Bracket plates cover smooth, rough or irregular shaped openings.

Each kit comes complete with brackets, sleeve, screws, identification labels and 3M™ Fire Barrier Moldable Putty+. Available in three sizes to cover a variety of installation needs.



3M™ Fire Barrier Putty Sleeve Kits

3M Fire Barrier Putty Sleeve Kits are designed for use in concrete floors, concrete walls, concrete block walls, and gypsum wall board.

Features and Benefits

- Designed to be used for both new construction and retrofitting
- System offers dual fire and cable through-penetration protection
- Kit includes all components required to meet firestop code for installation of cable and blank applications
- Rolled-out lip on sleeve facilitates smooth cable entry
- Brackets and sleeve work in tandem to help prevent slipping during installation — sleeve won't pull out
- Bracket plate covers smooth and rough irregular shaped openings to fit a variety of installation needs
- Red color for easy identification and inspection
- UL tested and fire rated up to 4 hours per ASTM E814 (UL1479)
- Economical — putty sleeve kits are versatile enough to help reduce inventory
- Available in three sleeve sizes: 1" (25mm), 2" (51mm) and 4" (102mm)



Label holds sleeve together until you need to retrofit around existing cables. Slit label to open sleeve. Close the two halves around the cables.



Bracket covers oversized openings (up to 3/4" [19mm] annular space). Innovative sleeve design assembles with the brackets to help prevent slipping during installation.



Installation of putty and application of identification label completes pass-through firestop. Putty holds cables in position, helping to prevent cable slippage and movement.

Ordering Information

3M™ Fire Barrier Putty Sleeve Kits

Product Number	Sleeve Size	Description/Kit Contains	Opening Size	UPC Number
DT100	1" (25mm)	One (1) Galvanized Steel Sleeve — 1"D x 12"L (25mm x 304mm) Two (2) Galvanized Steel Mounting Brackets — 3-3/8" x 3-3/8" (85mm x 85mm) Four (4) Hex Head Self-Drilling Screws — 3/4" (19mm) Eight (8) Coarse Thread Drywall Screws — 1-5/8" (41mm) Two (2) Installation Identification Labels 3M™ Fire Barrier Moldable Putty+ — Red	Min: 1-1/8" (29mm) Max: 2-1/4" (57mm)	000 51115 18809 1
DT200	2" (51mm)	One (1) Galvanized Steel Sleeve — 2"D x 12"L (51mm x 304mm) Two (2) Galvanized Steel Mounting Brackets — 5-1/4" x 5-1/4" (130mm x 130mm) Four (4) Hex Head Self-Drilling Screws — 3/4" (19mm) Eight (8) Coarse Thread Drywall Screws — 1-5/8" (41mm) Two (2) Installation Identification Labels 3M™ Fire Barrier Moldable Putty+ — Red	Min: 2-3/8" (60mm) Max: 4" (102mm)	000 51115 18808 4
DT400	4" (102mm)	One (1) Galvanized Steel Sleeve — 4"D x 12"L (102mm x 304mm) Two (2) Galvanized Steel Mounting Brackets — 8" x 8" (204mm x 204mm) Four (4) Hex Head Self-Drilling Screws — 3/4" (19mm) Eight (8) Coarse Thread Drywall Screws — 1-5/8" (41mm) Two (2) Installation Identification Labels 3M™ Fire Barrier Moldable Putty+ — Red	Min: 4-1/2" (114mm) Max: 6" (152mm)	000 51115 18806 0



LISTED
FIRESTOP DEVICES
9068



FIRESTOP DEVICE
FOR USE IN THROUGH-PENETRATION
FIRESTOP SYSTEMS
SEE UL FIRE RESISTANCE DIRECTORY
9068

Important Notice to User:

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M Fire Protection Product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



Building and Commercial Services Division

3M Center
Building 223-2N-21
St. Paul, MN 55144-1000
1-800-328-1687
www.3M.com/firestop

Please recycle. Printed in U.S.A.
© 3M 2010. All rights reserved.
98-0213-4607-1

3M is a trademark of 3M company.
All other trademarks are the property of their respective owners.